

"KL"

"H"

"L"

OPTIONS E,C

(EXPANSION ANCHORING APPLICATIONS)

- CLEARANCE MOUTING BASE

"M"

– Ø "I" –

OPTIONS A,C

(FOR EPOXY ANCHORING)

						NO OIL	BLACK OXIDE	BLACK OXIDE				EXPANSIO	N ANCHOR		EXPOXY	ANCHOR	
Α	В	С	D	Е	F	CL	AL	KL	Н	DIA I	DIA J	DRILL SIZE	MIN DEPTH	L	DRILL SIZE	MIN DEPTH	М
M20x1.5	050	13	38	28.6	10.3	255	110	N/A	25.4	50.8	38.1	N/A	N/A	N/A	10mm		140
M20 X 2.5	050	13	38	28.6	10.3	255	110	N/A	25.4	50.8	38.1	N/A	N/A	N/A	10mm	TBD.	140
M24 X 2	075	16	38	28.6	14.3	300	170	215	25.4	63.5	63.5	12.7	89	89	14mm	By By	155
M24 X 3	075	16	38	28.6	14.3	300	170	215	25.4	63.5	63.5	12.7	89	89	14mm	customer	155
M30 X 2	100	16	38	41.3	14.3	300	170	260	25.4	63.5	63.5	12.7	89	89	14mm	at install.	130
M30 X 3.5	100	16	38	41.3	14.3	300	170	260	25.4	63.5	63.5	12.7	89	89	14mm	at mstan.	130
M30 X 2	150	16	38	41.3	14.3	345	230	290	25.4	63.5	63.5	12.7	89	89	14mm		120
M30 X 3.5	150	16	38	41.3	14.3	345	230	290	25.4	63.5	63.5	12.7	89	89	14mm		120
M36 X 3	100	16	57	41.3	22.1	345	190	290	25.4	88.9	63.5	19	152	152	22mm		155
M36 X 4	100	16	57	41.3	22.1	345	190	290	25.4	88.9	63.5	19	152	152	22mm		155
M36X3	150	16	57	41.3	22.1	345	260	345	25.4	88.9	63.5	19	152	152	22mm	Click here	105
M36 X 4	150	16	57	41.3	22.1	345	260	345	25.4	88.9	63.5	19	152	152	22mm	for more	105
M39 X 3	100	16	57	41.3	22.1	345	230	290	25.4	88.9	63.5	19	152	152	22mm	info	155
M39 X 4	100	16	57	41.3	22.1	345	230	290	25.4	88.9	63.5	19	152	152	22mm		155
M39 X 3	150	16	57	41.3	22.1	345	260	345	25.4	88.9	63.5	19	152	152	22mm		105
M39 X 4	150	16	57	41.3	22.1	345	260	345	25.4	88.9	63.5	19	152	152	22mm		105

